

Fichte | Abete | Spruce

DIMENSION / I (mm)	AUFBAU / MODELLO/LAYERS			
48 x 88/95/120	DD	DKD		KK
72 x 75/95/105/120	DKD	DKK	D+DK	KKK
72 x 86				KKK
73 x 88	DKD	DKK	D+DK	KKK
75 x 95/125/145	DKD	DKK	D+DK	KKK
76 x 90	DKD	DKK	D+DK	KKK
83 x 88/95/105/120/125/145	DK(K)D	DK(K)K	D+D(K)K	KK(K)K
96 x 95/120/145	DKKD	DKKK	D+DKK	KKKK
97 x 88	DKKD	DKKK	D+DKK	KKKK
101 x 90	DKKD	DKKK	D+DKK	KKKK

Fett: Standardaufbau (inkl. der Keilzinkversionen 25+, 40+)

Neretto: *modello standard (compreso le versioni giuntate 25+,40+)*

Bold: standard layers (finger jointed versions 25+,40+)

Die Kanteln sind mit und ohne Fehlerzone erhältlich/*Il profilo lamellare e disponibile con e senza zona di possibile difetto*/The window scantling is available with or without possible defect zone

D = durchgehende Lage/*lamella intera*/continuous layers

K = keilgezinkte Lage/*lamella giuntata*/finger-jointed layers

Abstände Keilzinkung/*distanza giunzioni***/distance of finger joints:**

25cm+, 40cm+, 90cm+, 120cm+ (max. 150)

Längen/*lunghezze***/lengths:** 6 m = Standardlänge für keilgezinkte Ware/*lunghezza standard per prodotti giuntati*/ standard length for finger jointed products

Sonstige Längen unterhalb 6 m auf Anfrage/*altre misure inferiori ai 6 m su richiesta*/ other lengths under 6 m up on request

Trocknung/*essicazione***/drying:** 13% +/- 2%

EN 204 classe D4

PEFC -und FSC-zertifiziert/*certificato PEFC e FSC*/PEFC - and FSC certified

sarner leimholz

die Produktübersicht

lo schema prodotti

our product range

